Direct acting solenoid valves - Series P

Product code: P000-305-P5D

Datasheet creation date: 19/05/2026 16:53

Check the most updated document online click here




TECHNICAL DATA

Series	P
Body execution	0 = without subbase/conveyors
Number of seats	00 = without subbase/conveyors
Number of ways - Functions	3 = 3/2 way - NC
Valve connections	0 = ISO 15218 interface
Orifice diameter	5 = Ø 1.1 mm
Materials	P = PBT body - NBR - FKM - PU seals
Electrical connection	5 = industrial standard (9.4 mm)
Voltage - Absorbed power	D = 110 V 50/60 Hz - 2W
Fixing	= fixing screws for metal
Use with oxygen	= Not suitable for use with oxygen

Products designed for industrial applications. General terms and conditions for sale are available on www.camozzi.com.
This document contains a brief description of the products offered by Camozzi Automation at time of publication.
For more complete and up to date information about the Camozzi Automation product range, please refer to our online catalogue at https://shop.camozzi.com

Direct acting solenoid valves - Series P

Product code: P000-305-P5D



DIMENSIONS

Series	P
Body execution	0 = without subbase/conveyors
Number of seats	00 = without subbase/conveyors
Number of ways - Functions	3 = 3/2 way - NC
Valve connections	0 = ISO 15218 interface
Orifice diameter	5 = Ø 1.1 mm
Materials	P = PBT body - NBR - FKM - PU seals
Electrical connection	5 = industrial standard (9.4 mm)
Voltage - Absorbed power	D = 110 V 50/60 Hz - 2W
Fixing	= fixing screws for metal
Use with oxygen	= Not suitable for use with oxygen

Products designed for industrial applications. General terms and conditions for sale are available on www.camozzi.com.
This document contains a brief description of the products offered by Camozzi Automation at time of publication.
For more complete and up to date information about the Camozzi Automation product range, please refer to our online catalogue at https://shop.camozzi.com