Magnetic proximity switches, ATEX "II 3 GD" certified, T-slot, straight - Series CSG

Product code: CSG-223-5-EX

Datasheet creation date: 20/05/2026 09:27

Check the most updated document online click here




TECHNICAL DATA

Mod.	CSG-223-5-EX
Operation	Reed NO
Connection	2 wires
Voltage	5 ÷ 30 V AC/DC
Output	-
Max. current	100 mA
Max Load	3 W
Protection	IP67

Products designed for industrial applications. General terms and conditions for sale are available on www.camozzi.com.
This document contains a brief description of the products offered by Camozzi Automation at time of publication.
For more complete and up to date information about the Camozzi Automation product range, please refer to our online catalogue at https://shop.camozzi.com

Magnetic proximity switches, ATEX "II 3 GD" certified, T-slot, straight - Series CSG

Product code: CSG-223-5-EX



DIMENSIONS

Mod.	CSG-223-5-EX
Operation	Reed NO
Connection	2 wires
Voltage	5 ÷ 30 V AC/DC
Output	-
Max. current	100 mA
Max Load	3 W
Protection	IP67

Products designed for industrial applications. General terms and conditions for sale are available on www.camozzi.com.
This document contains a brief description of the products offered by Camozzi Automation at time of publication.
For more complete and up to date information about the Camozzi Automation product range, please refer to our online catalogue at https://shop.camozzi.com