ONE-TOUCH FITTINGS


Application

- One-touch joints used in pneumatic piping.
- Used for a wide variety of models to meet all needs.

Feature

- Easy to connect/disconnect tube by one touch.
- PC type is useful for piping in confined space, given its six-angle wrench processing inside.
- Elliptical sleeve makes it possible to apply and remove the tube easily in confined space.
- Fittings are equipped with a Gasket, O-ring and Teflon-Treatment already on the thread.

Structural Diagram



Specification

Fluid	Air(No other gases or liquids)	
Working Pressure Range	0~284PSI	0~20Kgf/㎠(0~1960kPa)
Negative Pressure	-29.5inHg	-750mmHg(10Torr)
Temperature Range	32~176℉	0~80℃
Applicable Tube Material	Polyurethane and Nylon	



Case In Use

▶ POC Model

- The hexagonal hole of the inside body makes it possible to tighten the fitting with a hexagonal wrench.
- A hexagonal wrench must be used due to the round exterior.

Product Code System

GPC 08 - 02 (①) (②) (③)

GPC 08 - 02 (GR) (①) (②) (③) (④)

① Type
② Tube Dia(ØD)

Code	04	06	08	10	12	16
Dia	Ø4	Ø6	Ø8	Ø10	Ø12	Ø16

③ Thread Size(T) *Metric Thread & R(PT) Thread

	Metric size		Taper Pipe Thread			
Code	M5	M6	01	02	03	04
Size	M5X0.8	M6X1.0	R1/8	R1/4	R3/8	R1/2

④ Color (Gray fitting can be produced)

	None	(GR)
Color	Black	Gray



⚠ CAUTION

- Be sure to read the "Common Precautions" and the "Using Precautions of Fitting Series" (P14) before using.
- In putting tube on the fitting, be sure to push it deeply into the inside. In case of incorrect installation, there is a risk of air leakage or loose tube.


⚠ WARNING

- Be sure to confirm that proper conditions are met(specifications), otherwise there may be air leakage by damage on the fitting body.

GPLJ

Plug-in Elbow





MODEL [ØD-T] Tube (Metric)-Thread(R) (mm)

CODE	MODEL	ØD1	ØD2	ØP	B	C1	C2	E	X	Y	Orifice (Ø mm)	W.G(g)	Q'ty/ Inbox
11140300	GPLJ 03	3	3	9	23.5	14.5	14.5	17.1	8.6	10.8	1.5	1.8	100
11140400	GPLJ 04	4	4	9	23.5	14.5	14.5	17.1	8.6	10.8	2.5	1.8	100
11140600	GPLJ 06	6	6	11.2	29.6	15.5	15.5	18	8.6	13	4	3	50
11140800	GPLJ 08	8	8	13.6	32.8	17.8	17.8	23.6	13	15	6	4.9	50
11141000	GPLJ 10	10	10	16.3	36.2	19.4	19.4	25	16	18.5	8	7.3	25
11141200	GPLJ 12	12	12	19.7	39.9	22.4	22.4	32.2	19.5	22.5	9	13.5	25
11141400	GPLJ 14	14	14	23.5	42.8	24.4	24.4	31.9	23	25	11	21.4	20
11141600	GPLJ 16	16	16	25.6	44.8	25	25	34	24	27	13	21.8	15