ONE-TOUCH FITTINGS


Application

- One-touch joints used in pneumatic piping.
- Used for a wide variety of models to meet all needs.

Feature

- Easy to connect/disconnect tube by one touch.
- PC type is useful for piping in confined space, given its six-angle wrench processing inside.
- Elliptical sleeve makes it possible to apply and remove the tube easily in confined space.
- Fittings are equipped with a Gasket, O-ring and Teflon-Treatment already on the thread.

Structural Diagram



Specification

Fluid	Air(No other gases or liquids)	
Working Pressure Range	0~284PSI	0~20Kgf/㎠(0~1960kPa)
Negative Pressure	-29.5inHg	-750mmHg(10Torr)
Temperature Range	32~176℉	0~80℃
Applicable Tube Material	Polyurethane and Nylon	



Case In Use

▶ POC Model

- The hexagonal hole of the inside body makes it possible to tighten the fitting with a hexagonal wrench.
- A hexagonal wrench must be used due to the round exterior.

Product Code System

GPC 08 - 02 (①) (②) (③)

GPC 08 - 02 (GR) (①) (②) (③) (④)

① Type
② Tube Dia(ØD)

Code	04	06	08	10	12	16
Dia	Ø4	Ø6	Ø8	Ø10	Ø12	Ø16

③ Thread Size(T) *Metric Thread & R(PT) Thread

	Metric size		Taper Pipe Thread			
Code	M5	M6	01	02	03	04
Size	M5X0.8	M6X1.0	R1/8	R1/4	R3/8	R1/2

④ Color (Gray fitting can be produced)

	None	(GR)
Color	Black	Gray



⚠ CAUTION

- Be sure to read the "Common Precautions" and the "Using Precautions of Fitting Series" (P14) before using.
- In putting tube on the fitting, be sure to push it deeply into the inside. In case of incorrect installation, there is a risk of air leakage or loose tube.


⚠ WARNING

- Be sure to confirm that proper conditions are met(specifications), otherwise there may be air leakage by damage on the fitting body.

GPUG

Different Dia of Union Tee





MODEL [ØD – T] Tube (Metric) – Thread(R) (mm)

CODE	MODEL	ØD1	ØD2	ØP1	ØP2	B	C1	C2	E	F1	F2	G	Ød	X1	Y1	X2	Y2	Orifice (Ø mm)	W.G(g)	Q'ty/ Inbox
11684300	GPUG 0604	6	4	11.2	9	37.9	15.5	14.5	19	6.5	6	18.1	3.2	11	13	8.6	11	3.2	6.2	50
11684400	GPUG 0804	8	4	13.6	11.2	47.2	17.8	14.5	23.6	8.5	8	19.6	3.2	13	15	8.6	11	3.2	12.1	50
11684500	GPUG 0806	8	6	13.6	11.2	47.2	17.8	15.5	23.6	8.5	8	20	3.2	13	15	11	13	5	10	50
11684600	GPUG 1006	10	6	16.3	13.6	50	19.4	15.5	25	10	9.5	23.5	4.2	16	19	11	13	5	18.3	25
11684700	GPUG 1008	10	8	16.3	13.6	50	19.4	17.8	25	10	9.5	24.1	4.2	16	19	13	15	7	14.7	25
11684900	GPUG 1208	12	8	19.7	16.3	64.4	22.4	17.8	32.2	12	10	25.1	4.2	19.5	23	13	15	7	30.1	25
11685000	GPUG 1210	12	10	19.7	16.3	64.4	22.4	19.4	32.2	12	10	25.5	4.2	19.5	23	16	19	9	25.6	20