

MODEL
NCEB

Fully adjustable needle valve with reverse flow check
SERIES 2 / CAPACITY: 45 L/min. (6,4 mm) / CAVITY: T-5A

sunhydraulics.com/model/NCEB





CONFIGURATION

L	Control	Standard Screw Adjustment
C	Reverse Flow Check	30 psi (2 bar)
N	Seal Material	Buna-N
(none)	Material/Coating	

Needle valves with reverse-flow check are fully adjustable orifices used to regulate flow. They are infinitely adjustable from fully closed up to the maximum orifice diameter. An integral high-capacity check valve provides unrestricted flow from port 2 to port 1. They are not pressure compensated.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-5A
Series	2
Capacity	45 L/min. (6,4 mm)
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min.
Adjustment - No. of CCW Turns from Fully Closed to Fully Open	5
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990203007
Seal kit - Cartridge	EPDM: 990203014
Seal kit - Cartridge	Viton: 990203006
Model Weight	0.27 kg.

NOTES

For Series 1 cartridges configured with an O control (panel mount handknob), a .75 in. (19 mm) diameter hole is required in the panel.

CONFIGURATION OPTIONS

Model Code Example: NCEBLCN


CONTROL (L)	REVERSE FLOW CHECK (C)	SEAL MATERIAL (N)	MATERIAL/COATING
L Standard Screw Adjustment	**C** 30 psi (2 bar)	**N** Buna-N	Standard Material/Coating
H Calibrated Handknob with Detent Lock	**A** 4 psi (0,3 bar)	**E** EPDM	**/AP** Stainless Steel, Passivated
K Handknob	**E** 75 psi (5 bar)	**V** Viton	**/LH** Mild Steel, Zinc-Nickel
Y Tri-Grip Handknob			


© 2025 Sun Hydraulics


TECHNICAL FEATURES


- All 2-port flow control cartridges are physically and functionally interchangeable (i.e. same flow path, same cavity for a given frame size). However, cartridge extension dimensions from the mounting surface may vary.
- Because needle valves are non-compensating devices, the fixed orifice size will regulate flow through the valve in proportion to the square root of the pressure differential across ports 1 and 2.
- A balanced adjustment mechanism allows for easy adjustment even at high pressures.
- The sharp-edged orifice design minimizes flow variations due to viscosity changes.
- Cartridges configured with EPDM seals are for use in systems with phosphate ester fluids. Exposure to petroleum based fluids, greases and lubricants will damage the seals.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

PERFORMANCE CURVES









© 2025 Sun Hydraulics