




TECHNICAL DATA

Body Type	Line mount
Interface	1.25 SAE C61
Body Features	Direct mount
Open Cavities	1
Cavity	T-17A
Port Size	1 1/4" Code 61
Model Weight	1.53 kg.

NOTES

Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

© 2026 Sun Hydraulics

PORT DESIGNATORS

Modifiers	Ports
WDJ, /10, /11, /15, /16, /V	Ports 1 & 2: 1 1/4" Code 61; All Other Ports: SAE 4;

INCLUDED COMPONENTS

Part	Description	Quantity
500-001-222	O-Ring	1

CONFIGURATION OPTIONS
Model Code Example: WDJArray

MODIFIER

6061-T651 Aluminum, Buna-N

/10 6061-T651 Aluminum, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II

/11 6061-T651 Aluminum, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I

/15 6061-T651 Aluminum, Viton, Black Anodize - Per MIL SPEC 8625F Type II, Class II

/16 6061-T651 Aluminum, Viton, Clear Anodize - Per MIL SPEC 8625F Type II, Class I

/V 6061-T651 Aluminum, Viton

/S 65-45-12 Ductile Iron, Buna-N, Dewatering Oil

/S3 65-45-12 Ductile Iron, Buna-N, Trivalent Clear Zinc with Top Sealer

/S4 65-45-12 Ductile Iron, Buna-N, Chem. Black

/S5 65-45-12 Ductile Iron, Buna-N, Electroless Nickel

/Y 65-45-12 Ductile Iron, Viton, Dewatering Oil

/Y1 65-45-12 Ductile Iron, Viton, Clear Zinc Nickel with Top Sealer

/Y3 65-45-12 Ductile Iron, Viton, Trivalent Clear Zinc with Top Sealer

/Y4 65-45-12 Ductile Iron, Viton, Chem. Black

/Y5 65-45-12 Ductile Iron, Viton, Electroless Nickel


MANIFOLD FACES

FACE GRID




© 2026 Sun Hydraulics

Face 2




Face 5




© 2026 Sun Hydraulics

Face 6




Face 7



© 2026 Sun Hydraulics

Face 8



© 2026 Sun Hydraulics