

TECHNICAL DATA

Body Type	Motor mount
Interface	Eaton/Char-Lynn 4000/6000
Body Features	Cross pilot
Open Cavities	2
Cavity	T-2A
Port Size	3/4" Code 61
Model Weight	1.34 kg.

NOTES

Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

© 2026 Sun Hydraulics

PORT DESIGNATORS

Modifiers	Ports
VZX, /10, /11, /15, /16, /V	Port Size: 3/4" Code 61;
VZX/1A, /1B, /1F, /1G, /M, /Z	Port Size: 1" BSPP;

INCLUDED COMPONENTS

Part	Description	Quantity
500-001-214	O-Ring	2
A330-006-002	Sub-assembly	2

CONFIGURATION OPTIONS
Model Code Example: VZXArray

MODIFIER

6061-T651 Aluminum, Buna-N

/10 6061-T651 Aluminum, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II

/11 6061-T651 Aluminum, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I

/15 6061-T651 Aluminum, Viton, Black Anodize - Per MIL SPEC 8625F Type II, Class II

/16 6061-T651 Aluminum, Viton, Clear Anodize - Per MIL SPEC 8625F Type II, Class I

/1A 6061-T651 Aluminum, Metric, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II

/1B 6061-T651 Aluminum, Metric, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I

/1F 6061-T651 Aluminum, Metric, Viton, Black Anodize - Per MIL SPEC 8625F Type II, Class II

/1G 6061-T651 Aluminum, Metric, Viton, Clear Anodize - Per MIL SPEC 8625F Type II, Class I

/M 6061-T651 Aluminum, Metric, Buna-N

/V 6061-T651 Aluminum, Viton

/Z 6061-T651 Aluminum, Metric, Viton

/S 65-45-12 Ductile Iron, Buna-N, Dewatering Oil

/S3 65-45-12 Ductile Iron, Buna-N, Trivalent Clear Zinc with Top Sealer

/S4 65-45-12 Ductile Iron, Buna-N, Chem. Black

/S5 65-45-12 Ductile Iron, Buna-N, Electroless Nickel

/T 65-45-12 Ductile Iron, Metric, Buna-N, Dewatering Oil

/T3 65-45-12 Ductile Iron, Metric, Buna-N, Trivalent Clear Zinc with Top Sealer

/T4 65-45-12 Ductile Iron, Metric, Buna-N, Chem. Black

/T5 65-45-12 Ductile Iron, Metric, Buna-N, Electroless Nickel

/W 65-45-12 Ductile Iron, Metric, Viton, Dewatering Oil

/W3 65-45-12 Ductile Iron, Metric, Viton, Trivalent Clear Zinc with Top Sealer

/W4 65-45-12 Ductile Iron, Metric, Viton, Chem. Black

/W5 65-45-12 Ductile Iron, Metric, Viton, Electroless Nickel

/Y 65-45-12 Ductile Iron, Viton, Dewatering Oil

/Y3 65-45-12 Ductile Iron, Viton, Trivalent Clear Zinc with Top Sealer

/Y4 65-45-12 Ductile Iron, Viton, Chem. Black

/Y5 65-45-12 Ductile Iron, Viton, Electroless Nickel


MANIFOLD FACES

FACE GRID

© 2026 Sun Hydraulics


5	6	7	8
9	10	11	12

Face 2




© 2026 Sun Hydraulics

Face 5




© 2026 Sun Hydraulics

Face 6




© 2026 Sun Hydraulics

Face 7




© 2026 Sun Hydraulics

Face 8



Face 10



© 2026 Sun Hydraulics