

MODEL
XEOA

Port 1 to 2 open, port 3 blocked cavity plug
SERIES 1 / CAVITY: T-11A

sunhydraulics.com/model/XEOA





CONFIGURATION

X	Control	-
X	Adjustment Range	-
N	Seal Material	Buna-N
(none)	Material/Coating	

This cavity plug allows ports 1 and 2 to remain open and blocks port 3.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-11A
Series	1
Port Configuration	3 Port
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Seal kit - Cartridge	Buna: 990011007
Seal kit - Cartridge	EPDM: 990011014
Seal kit - Cartridge	Polyurethane: 990011002
Seal kit - Cartridge	Viton: 990011006
Model Weight	0.09 kg.

CONFIGURATION OPTIONS

Model Code Example: XEOAXXN

CONTROL (X)	ADJUSTMENT RANGE (X)	SEAL MATERIAL (N)	MATERIAL/COATING
X -	**X** -	**N** Buna-N	Standard Material/Coating
		E EPDM	**/AP** Stainless Steel, Passivated
		V Viton	**/LH** Mild Steel, Zinc-Nickel

TECHNICAL FEATURES

- Corrosion resistant cavity plugs are intended for use in corrosive environments and are identified by the model code suffix /AP (see CONFIGURATION section). The bodies of these plugs are made from high strength lean duplex stainless steel. Internal parts are made from carbon steel leaded alloy, the same as standard plugs.

RELATED MODELS

- XEOAE Model

© 2025 Sun Hydraulics