




CONFIGURATION

/S	Modifier	65-45-12 Ductile Iron, Buna-N, Dewatering Oil

TECHNICAL DATA

Body Type	Line mount
Interface	None
Body Features	Inline, cross pilot
Mounting Hole Diameter	.34 in.
Mounting Hole Depth	Through
Mounting Hole Quantity	2
Open Cavities	2
Cavity	T-11A
Port Size	3/8" BSPP
Model Weight	3.77 lb.

NOTES

Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

PORT DESIGNATORS

Modifiers	Ports
XEU, /10, /11	All Ports: 3/8" BSPP;

CONFIGURATION OPTIONS
Model Code Example: XEU/S

MODIFIER (/S)

/S 65-45-12 Ductile Iron, Buna-N, Dewatering Oil
6061-T651 Aluminum, Buna-N

/11 6061-T651 Aluminum, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I

/10 6061-T651 Aluminum, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II

/S4 65-45-12 Ductile Iron, Buna-N, Chem. Black

/S3 65-45-12 Ductile Iron, Buna-N, Trivalent Clear Zinc with Top Sealer

/A 316 Stainless Steel, Buna-N


MANIFOLD FACES

FACE GRID

© 2026 Sun Hydraulics


1	2	3	4
5	6	7	8
9	10	11	12

Face 2




© 2026 Sun Hydraulics

Face 5




© 2026 Sun Hydraulics

Face 6




© 2026 Sun Hydraulics

Face 7



Face 8

Face 10



© 2026 Sun Hydraulics