




TECHNICAL DATA

Body Type	Gasket mount
Interface	Sun
Body Features	Inline, Direct mount, cross pilot, 2 gasket ports
Mounting Hole Diameter	.42 in.
Mounting Hole Depth	Through
Mounting Hole C'bore Diameter	.59 in.
Mounting Hole Quantity	3
Open Cavities	2
Cavity	T-11A
Port Size	SAE 8
Model Weight	1.13 lb.

NOTES

Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

© 2025 Sun Hydraulics

PORT DESIGNATORS

Modifiers	Ports
XVO, /10, /11, /15, /16, /V	Ports V1 & V2: SAE 8;

INCLUDED COMPONENTS

Part	Description	Quantity
500-001-113	O-Ring	2

CONFIGURATION OPTIONS
Model Code Example: XVO

MODIFIER

6061-T651 Aluminum, Buna-N

/11 6061-T651 Aluminum, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I

/10 6061-T651 Aluminum, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II

/V 6061-T651 Aluminum, Viton

/16 6061-T651 Aluminum, Viton, Clear Anodize - Per MIL SPEC 8625F Type II, Class I

/15 6061-T651 Aluminum, Viton, Black Anodize - Per MIL SPEC 8625F Type II, Class II

/S 65-45-12 Ductile Iron, Buna-N, Dewatering Oil

/S4 65-45-12 Ductile Iron, Buna-N, Chem. Black

/S3 65-45-12 Ductile Iron, Buna-N, Trivalent Clear Zinc with Top Sealer

/Y 65-45-12 Ductile Iron, Viton, Dewatering Oil

/Y4 65-45-12 Ductile Iron, Viton, Chem. Black

/Y3 65-45-12 Ductile Iron, Viton, Trivalent Clear Zinc with Top Sealer


MANIFOLD FACES

FACE GRID




© 2025 Sun Hydraulics

Face 2




© 2025 Sun Hydraulics

Face 5



© 2025 Sun Hydraulics


Face 6



Face 7


© 2025 Sun Hydraulics

Face 8



© 2025 Sun Hydraulics

Face 10



© 2025 Sun Hydraulics