

MODEL
770924N


24 VDC coil with Deutsch DT04-2P connector without TVS Diode

sunhydraulics.com/model/770924N





DC Coil – No Diode



TECHNICAL DATA

Maximum Coil Temperature at 68ºF (20ºC) Ambient	218ºF (105ºC)
Arc Suppression (TVS)	None
Power Consumption (cold) - at rated voltage	22 watts
Maximum Ambient Temperature	50 °C
Voltage/Frequency	24 VDC
Operating Voltage Range	+/- 10% nominal
Duty Cycle Rating	100 %
Connector	Deutsch DT04-2P
Connector Environment Rating	IP69K
Solenoid Tube Diameter	19 mm
Coil Nut Torque	0,5 Nm
Model Weight	0.24 kg.

PROPORTIONAL PERFORMANCE DATA

Maximum Current	590 mA
Nominal Coil Resistance at 122ºF (50ºC) Stabilized	37.2 ±5% ohms
Nominal Coil Resistance at 68ºF (20ºC) Cold	26.2 ±5% ohms

USED WITH

DMDA	DMDAS	DNCA	DNDA	DNDAS	DNDC	DNDY	DNDYS	FMDA	FMDB
FPCC	FPCH	FPFK	FPHK	HDDA	PRDM	PRDN	PSDL	PSDP	RBAN
RBAP	991723001	991723002							

© 2025 Sun Hydraulics

TECHNICAL FEATURES

- This DC coil does not include a TVS surge suppression diode. Coils without TVS diodes should only be used when surge suppression is included elsewhere in the electrical system.
- The coil is magnetically symmetrical and can be mounted in either direction on the solenoid tube without affecting performance.
- For optimum proportional performance, an amplifier with current sensing and adjustable dither should be used. Dither should be adjustable between 100 - 250 Hz.
- Coil windings utilize Class N, (392° F [200 °C] rated) magnet wire.
- The external steel shell is plated with clear zinc trivalent.
- The Deutsch DT04-2P connector satisfies the requirements of thermal shock tests. In this test, the coil is energized to achieve its stabilized temperature and then immediately immersed into ice cold water. This process is repeated 5 times, after which, the insulation resistance of the coils should not fall below 10 megohms.
- IP rating is dependent on the coil connector and the mating connector used.
- Power cable with mating connector is required and is not included with product.
- RoHS compliant. Restricted materials less than 0.1% total by weight.

© 2025 Sun Hydraulics