




CONFIGURATION

/S3 Modifier	65-45-12 Ductile Iron, Buna-N, Trivalent Clear Zinc with Top Sealer

TECHNICAL DATA

Body Type	Line mount
Interface	None
Body Features	Cross pilot
Mounting Hole Diameter	.42 in.
Mounting Hole Depth	Through
Mounting Hole Quantity	2
Open Cavities	2
Cavity	T-2A
Port Size	3/4" BSPP
Model Weight	6.88 lb.

NOTES

Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

PORT DESIGNATORS

Modifiers	Ports
YAW, /10, /11, /S, /S3	Ports C1, C2, V1, V2: 3/4" BSPP;

CONFIGURATION OPTIONS
Model Code Example: YAW/S3

MODIFIER **(/S3)**

/S3 65-45-12 Ductile Iron, Buna-N, Trivalent Clear Zinc with Top Sealer
6061-T651 Aluminum, Buna-N
/11 6061-T651 Aluminum, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
/10 6061-T651 Aluminum, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II
/S 65-45-12 Ductile Iron, Buna-N, Dewatering Oil
/S4 65-45-12 Ductile Iron, Buna-N, Chem. Black

MANIFOLD FACES


FACE GRID

1 2 3 4


© 2026 Sun Hydraulics

5	6	7	8
9	10	11	12

Face 2




Face 5




© 2026 Sun Hydraulics

Face 6




Face 7



© 2026 Sun Hydraulics

Face 10



© 2026 Sun Hydraulics